

CHOICE® ALUMINIZED FABRICS

11TT417-AL7

A Norfab woven fabric of an Aramid fiber blend over an oxidized PAN (OPF) and fiberglass core yarn, aluminized one side. Applications include safety clothing, gloves, mitts, jackets, curtains and other industrial applications. Resistant to radiant heat sources, offers excellent thermal protection for safety garments.

About NOR*FAB Corporation

NOR*FAB manufactures textile products using flame resistant synthetic fibers suited for use at high temperatures and for personal protection. These items include broad woven roll goods and narrow products in the form of woven and knitted tapes, sleeving, rope, and gasketing. NOR*FAB uses para-aramid, meta-aramid, melamine, phenolic, oxidized PAN, flame resistant rayon, polybenzimidazole, and other technical fibers blended into unique yarns which provide high levels of heat protection and insulation.

NOR*FAB produces many of these yarns on the DREF Spinning System for use in the weaving, knitting, gasket, and wire & cable industries. NOR*FAB possesses the largest collection of DREF III spinning frames of any yarn manufacturer in the world.

Among its offerings, NOR*FAB boasts fabric lines for the following end uses:

Firefighting

OMNI Vantage™, OMNI Elite®, OMNI 45™, and OMNI Quilt™

Electric Arc Protection

NF Arc™, ArcWeld®

Welding Protection

ArcWeld®

Cut Protection

CutPro®

Molten Metal Splash Protection

Choice®

Since 1979

Proud American Manufacturers of Flame Resistant Textiles

NORFAB AL7 Aluminized Fabric Data Sheet

Style	11TT417-AL7
Base Fabric	Aramid /OPF/ Fiberglass
Color/Appearance	Yellow + Black, Aluminized 1 side
Style	Twill
Fabric Weight (oz/yd², average)	14 oz (475 gm/m ²)
Fabric Thickness, (in)	0.030
Warp Strength (lbs) (1" unraveled)	270
Fill Strength (lbs) (1" unraveled)	215
Flammability-After Flame (seconds)	2
Flammability- Char length (inches)	0.25
Adhesion after Wet Flex	Pass
Reflectivity after Abrasion (seconds) (ASTM F1939)	34
RPP Rating (cal/cm²)	68
Taber Abrasion	1400
Molten Iron Splash (ASTM F955)	Pass
Molten Aluminum Splash (ASTM F955)	Pass
Other Certifications	ISO 11612-2015 A1, A2, B1, C3, D3, E3, F2

All data +/- 10%. All data intended as general information and no warranties, guarantees, or claims of fitness for use are expressed or implied by NOR*FAB Corp. 514



1310 Stanbridge Street,

Box 830, Norristown, PA 19404-0830 U.S.A.

Tel: 610-275-7270 • 800-441-9680 • Fax: 610-277-6106

Email: sales@norfab.com • www.norfab.com